

## AC3.5kW~7kW~11kW PORTABLE CHARGING PILE

### Features

- ① IP65 waterproof, dustproof, and resistant to salt spray
- ① Automatic temperature detection
- ① CE and FCC Certification
- ① 6 measures for safety protection
- ① Compatible with 99.9% of electric vehicles
- ① Adaptive power control



## SPECIFICATIONS

Working Temperature	-25°C~55°C	
Storage Temperature	-30°C~85°C	
Working Humidity	5~95%, No condensation	
Output Voltage	110V AC/220V AC/240V AC/480V AC	
Operating Voltage	110V/220V/240V/480V	
Output Frequency	50Hz-60Hz	
Output Current	16A/32A/40A	
Output Current	16A 1P/3P:6/8/10/13/16A 32A 1P/3P:6/8/10/13/16/20/32A 40A:6/8/10/13/16/20/32/40A	
Insulation Resistance	> 10MΩ	
Altitude	≤2000m	
Atmospheric Pressure	80kPa ~101kPa	
IP Level	Control box IP65	
	Plug on car(unconnected) IP54	
	Plug on car(connected) IP55	
Total Cable Length	5m or customized	
Weight	≤2.2kg	
Control Pilot	Duty ratio	53.3%
	Frequency	1000Hz
Leakage Protection	Type A+DC(Type B)	
	AC leakage	20/30mA
	DC leakage	6mA(optional)
Insulation Resistance	> 10MΩ	