

## DC20kW~30kW~40kW WALL-MOUNTED CHARGING PILE

### Features

- ① Security protection, charging control management, communication and other functions
- ① Settings for automatic charging and manual charging modes
- ① Realize the management of human-computer interaction and charging control
- ① Mildew-proof, salt spray-proof, dustproof, and waterproof, etc.
- ① Having a good human-computer interaction experience, the operation is easy
- ① Perfect scalability and good compatibility
- ① Compliance with national, industry, or corporate standards



### SPECIFICATIONS

AC Input Voltage	400VAC +/-10%/3Phase+PE
AC Input Frequency	45Hz/65Hz
Max Input Current	80A
Output Power	20kW~30kW~40kW
Output Voltage Range(DC)	200-500VDC/200-1000VDC
Output Current	0-66A, 0-133A
Navigation	Voice navigation throughout the operation, fault prompt
Optional Function	Credit card/RFID
Display Function	4.3 Inch true color capacitive touch screen
Cable Length	5m (Can be customized)
Efficiency	Fully loaded state≥95%
Auxiliary Power	12V/24V
Working Temperature	-40~85°C, 25°C (TYPE); Intelligent derate if the case
Protection Level	IP54
Size	Wall-Mounted:548×378× 250mm
Weight	42kg
OCPP	JSON 1.6 (optional)
Charging Interface	CCS1/CCS2/CHAdeMO/GB/T compatible