

60kW~120kW~150kW FLOOR TYPE AC&DC INTEGRATED

Features

- ⑤ Support European standard CCS2, American standard CCS1, Chinese standard GB/T, Janpanese standard CHAdeMO
- ⑤ ISO15118/DIN70121, IEC61851, SAE-J1772, IEC62196
- ⑤ OCPP1.6 (networked version), Intelligent charging charging power
- ⑤ Distribution load management
- ⑤ 7-inch capacitive touch LCD
- ⑤ Power module IP54 protection



SPECIFICATIONS

Charging Mode	RFID, Plug and Charge, APP(OCPP)
Size	1675*705*545mm
Weight	≤268kg
Cable Length	5m (can be customized)
Plug Standard	CHAdeMO or CCS1 or CCS2 or GB/T
Protection Level	IP54
Cooling Method	Wind cooling
Standard:LAN Optional:WIFI、4G	Server communication, APP communication
OCPP	OCPP 1.6J/1.5J
AC Input Voltage	400VAC +/-10%/3Phase+PE
AC Input Frequency	45Hz/65Hz
Input Current	Each Phase 0~114A
Leakage Protection	Type A 100mA
Operating Temperature	-20°C~60°C
Output Voltage	DC 150V~1000V
Output Current	60kW DC 0~120A
LED Indicator	Charging green, Fault red, Standby blue
LCD	7 Inch HD high-brightness industrial resistance display